



ALUMINIUM BI-FOLDING DOORS QUOTE REQUEST

Full Name: ----- Company: -----

Address: -----

Postcode: -----

Telephone: ----- Fax: -----

Mobile: ----- Email: -----

Site Delivery Postcode: -----	Job Reference: -----
<i>*glass delivery surcharge may apply</i>	
Products must comply to thermal and ventilation performance requirements in line with current Document L and F Legislation. MFT supply compliant product for both New Build and Renovation products.	
*Project installation type: (*compulsory field)	New Build <input type="checkbox"/> Renovation / Replacement <input type="checkbox"/>

Indicates sash direction **Width:** ----- **Height:** -----

including cill

Viewed from the outside

Minimum sash width: 600mm*. Maximum sash width: 1250mm. Max height: 2500mm

*Minimum door width of 600mm only available on configurations with a traffic door, otherwise 700mm minimum sash width applies

Glazing: (28mm units)

New Build Compliant

U 1.1 Clear Laminated

Renovation / Replacement Compliant

Clear Toughened
 Clear Laminated

Buyer responsible for compliance

Unglazed

Integral blind glass options

Renovation / Replacement Compliant

Centre pane U=1.2 W/m²K

28mm clear low E
 Laminated with clear low E (PAS24)

New Build Compliant

Centre pane U=1.0 W/m²K

Laminated with solar control

Slat colours

S102 White* S149 Cream*
 S157 Silver* S155 Grey
 S156 Metallic silver S125 Beige
 S142 Light blue S130 Green
 B160 Black S159 Anthracite grey

*When the laminated glass option is chosen the only slat colours available are S102 White, S149 Cream & S157 Silver

Slider, sideguide & headrail colour

White Beige Black
 Light grey Anthracite grey

*When the laminated glass option is chosen only slider, sideguide & headrail colours available are White, Beige & Light Grey

Operation magnet position
when viewed from the inside

Left side of sash
 Right side of sash

Standard colours

White - Gloss (RAL 9910) Anthracite Grey - Matt (RAL 7016) Black - Matt (RAL 9005) Agate Grey - Matt (RAL 7038)
 Agate Grey - Matt, external (RAL 7038) / White - Gloss, internal (RAL 9910) Black - Matt, external (RAL 9005) / White - Gloss, internal (RAL 9910)
 Anthracite Grey - Matt, external (RAL 7016) / White - Gloss, internal (RAL 9910)

Special colours RAL / BS + finish

External RAL/BS colour:	<input type="checkbox"/> Satin <input type="checkbox"/> Matt	Internal RAL/BS colour:	<input type="checkbox"/> Satin <input type="checkbox"/> Matt
	<input type="checkbox"/> Gloss		<input type="checkbox"/> Gloss

Threshold

Standard
 150mm Integrated cill threshold (open out only)

Opening

Open in Open out

Notes

Outside access unavailable without a traffic door.
We do not offer a wheelchair specific threshold option.
PAS 24 as standard

Cill

None 100mm
 150mm 190mm

Frame extender

20mm 40mm

Top
 Left Right

Trickle vent (s)

1 2 3 4

Frame extender not required for trickle vents
***2667mm² airflow per vent**
Buyer is responsible for ensuring Doc F ventilation compliance. If in doubt choose 3 vents.

Furniture

White Black Chrome
 Grey Brushed stainless steel
 Grey/White Black/White

Delivery

Assembled Kit form

Note:
Please ensure that the purchasing company have sufficient able bodied representatives available at the delivery address to assist with the offloading of the products. If this is not met you may be charged for re-delivery of both product and glass



Email quote to: sales@madefortrade.co Tel: 01642 610799