



ALUMINIUM BI-FOLDING DOORS QUOTE REQUEST

Full Name: _____ Company: _____

Address: _____

Postcode: _____

Telephone: _____ Fax: _____

Mobile: _____ Email: _____

Site Delivery Postcode: _____ Job Reference: _____

**glass delivery surcharge may apply*

Products must comply to thermal and ventilation performance requirements in line with current Document L and F Legislation. MFT supply compliant product for both New Build and Renovation products.

***Project installation type:** (**compulsory field*) New Build Renovation / Replacement

Indicates sash direction Width: _____ Height: _____

→

including cill

Viewed from the outside

Notes:

Glazing: (28mm units)

New Build Compliant

U 1.1 Clear Laminated

Renovation / Replacement Compliant

Clear Toughened

Clear Laminated

Buyer responsible for compliance

Unglazed

Minimum sash width: 600mm*. Maximum sash width: 1250mm. Max height: 2500mm

*Minimum door width of 600mm only available on configurations with a traffic door, otherwise 700mm minimum sash width applies

Standard colours

White gloss (RAL 9910) Grey matt (RAL 7016) Black matt (RAL 9005)

Grey matt external (RAL 7016) / White gloss internal (RAL 9910)

Special colours RAL / BS + finish

External RAL/BS colour:	<input type="checkbox"/> Satin <input type="checkbox"/> Matt	Internal RAL/BS colour:	<input type="checkbox"/> Satin <input type="checkbox"/> Matt
	<input type="checkbox"/> Gloss		<input type="checkbox"/> Gloss

Integral blind glass options

Renovation / Replacement Compliant

4-20-4 Planitherm Total +

4-20-4 Planiclear Cool Lite SKN176

4-16-7.8 Planiclear Cool Lite SKN176

New Build Compliant

4-16-7.8 Planiclear Cool Lite SKN176 Laminated

Threshold

Standard

150mm Integrated cill threshold (open out only)

Cill

None 100mm

150mm 190mm

Furniture

White Black Chrome

Grey Brushed stainless steel

Grey/White Black/White

Slat colours

White Cream Silver Grey

Metallic silver Beige Light blue

Green Black Anthracite grey

Opening

Open in Open out

Frame extender

20mm 40mm

Top

Left Right

Delivery

Assembled Kit form

Slider, slideguide & headrail colour

White Beige Black Light grey

Anthracite grey

Notes

Outside access unavailable without a traffic door.

We do not offer a wheelchair specific threshold option.

PAS 24 as standard

Trickle vent (s)

1 2 3 4

Frame extender not required for trickle vents

***2667mm² airflow per vent**

Buyer is responsible for ensuring Doc F ventilation compliance. If in doubt choose 3 vents.

Note:

Please ensure that the purchasing company have sufficient able bodied representatives available at the delivery address to assist with the offloading of the products. If this is not met you may be charged for re-delivery of both product and glass

Operation magnet position when viewed from the inside

Left side of sash

Right side of sash



Email quote to: sales@madefortrade.co Tel: 01642 610799